



未注公差/General tolerances (mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10 ±2'
~	~	~	~	~	~	~	~	~	~	~	~	~	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

额定电流/Rated current	10A
额定电压/Rated voltage	300V
线圈/触点介质耐压/Coil/Contact dielectric voltage	3000V/S
触点间介质耐压/Dielectric voltage between contact	2500V/S
螺钉扭矩/Screw torque	1.2Nm
外连接导线/External connection wire	20-14/0.5-2.5WG /mm²
环境温度/Ambient temperature	-40~+65°C
重点管控符号/Key controlled symbol	*
符合RoHS环保要求/Conform to RoHS	
印字为激光打标, 印字内容清晰、无断线等/Printing for laser marking, printing content is clear, no broken line, ect	
印字面按图中脚位参考/Seal literal reference according to the foot position in the drawing	

备注: 1个产品配有3个附件, 如下图所示;  
 Note: 1 product is equipped with 3 accessory, a s shown below;



		MATERIAL:	SURFACE/COLOR:		
		MAT NO./REV: 30020000054-1 / 00.05	MAT STATUS: 小批量		
APPD: 李根芳	2025.08.04	NAME			
CHKD: 浦瀚	2025.07.31	DPTF14A-3-00Z (H)			
DRFT: 龚新建	2025.07.30				
DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET	
200287831	CUSTOMER DRAWING	已发布	1:1	1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
01		Change: Revise CE printing	龚新建	2025.07.30

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in general. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、软件著作权等知识产权外, 本公司保留对涉及发明、实用新型及外观设计专利的所有权利。